

MARSON SY 2



Grease

Multipurpose synthetic grease.

APPLICATIONS

- Can be used in all lubrication systems under pressure.
- For lubrication of all heavily loaded bearings and rails.
- For anti-roll bar bushing.

SPECIFICATIONS

- ISO-L-X DCEA 2
- DIN 51502 MPPG2K-40
- PSA STL 71 3410

ADVANTAGES

- Synthetic grease (polyalkyleneglycol base oil).
- Good resistance to high loads and shocks.
- Long service life.
- High thermal stability.
- Compatible with most used elastomers.

TYPICAL CHARACTERISTICS	METHODS	UNITS	MARSON SY 2
Texture	Visual	-	Smooth
Colour	Visual	-	Cream
NLGI grade	ASTM D 217/DIN 51 818	-	2
Dropping point	IP 396/DIN ISO 2176	°C	> 180
Soap	-	-	Lithium
Kinematic viscosity of the base oil at 40°C	ASTM D 445/DIN 51 562-1/ISO 3104/IP71	mm ² /s (cSt)	140
Operating temperature range	-	°C	- 40 to 120 °C
Penetration at 25 °C	IP 396/NFT 60 102 C	-	265 - 295

Above characteristics are mean values given as an information.

TOTAL LUBRIFIANTS
Industrie & Spécialités
8-11-2005 (supersedes 05-04-2004)
MARSON SY 2
1/1



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. is obtainable via your commercial adviser www.quick-fds.com.