

Klüberfood NH1 94-402

Synthetic special lubricating grease for the food processing and pharmaceutical industries



Benefits for your application

- **Increased component availability and extended maintenance intervals**
 - owing to its good load-carrying capacity
 - due to good corrosion protection
- **Reduces friction and wear, e.g. in rolling bearings, owing to its good wear protection properties and good flow characteristics.**
- **ISO 21469 certified- supports the compliance with hygienic requirements in your production plant. You will find further information on ISO standard 21469 on our website www.klueber.com**

Description

Klüberfood NH1 94-402 is a special lubricating grease composed of a highly refined base oil and a calcium complex thickener.

The use of Klüberfood NH1 94-402, an NSF H1-registered lubricant, can contribute to a safe product regime when used in accordance with food manufacturing regulations.

Klüberfood NH1 94-402 is NSF H1 registered and therefore comply with FDA 21 CFR § 178.3570. The lubricant was developed for incidental contact with products and packaging materials in the food-processing, cosmetics, pharmaceutical or animal feed industries. The use of Klüberfood NH1 94-402 can contribute to increase reliability of your production processes. We nevertheless recommend conducting an additional risk analysis, e.g. HACCP.

Application

Klüberfood NH1 94-402 is used for the lubrication of rolling bearings of machines and installations used in the food-processing industry, e.g. in the manufacture of grain, meal and pellet animal feeds.

Application notes

Klüberfood NH1 94-402 is applied by standard commercial grease application equipment, e.g. spatula, grease gun.

Before applying Klüberfood NH1 94-402, all lubrication points should be thoroughly cleaned to ensure maximum hygiene conditions exist, mandatory for food-safe H1 lubrication.

If the production process does not allow cleaning, we recommend the existing grease be replaced by purging the system during re-lubrication.

Please do not hesitate to contact our Technical Consulting and Sales Departments in respect of grease miscibility, re-lubrication procedures etc.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Pack sizes	Klüberfood NH1 94-402
Can 1 kg	+
Bucket 25 kg	+
Drum 180 kg	+

Product data	Klüberfood NH1 94-402
Article number	096097
NSF-H1 registration	139 051
Lower service temperature	-30 °C / -22 °F
Upper service temperature	160 °C / 320 °F



Klüberfood NH1 94-402

Synthetic special lubricating grease for the food processing and pharmaceutical industries

Product data	Klüberfood NH1 94-402
Colour space	beige
Texture	homogeneous
Density at 20 °C	approx. 0.97 g/cm ³
Worked penetration, DIN ISO 2137, 25 °C, lower limit value	280 x 0.1 mm
Worked penetration, DIN ISO 2137, 25 °C, upper limit value	310 x 0.1 mm
Kinematic viscosity of the base oil, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 40 °C	approx. 400 mm ² /s
Kinematic viscosity of the base oil, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 100 °C	approx. 40 mm ² /s
Corrosion inhibiting properties of lubricating greases, DIN 51802, (SKF-EMCOR), test duration: 1 week, distilled water	<= 1 corrosion degree
Oil separation, ASTM D 6184 [FTMS 791 C 321], after 30 h/100 °C	<= 4 % by weight
Flow pressure of lubricating greases, DIN 51805, test temperature: -30 °C	approx. 1 400 mbar
Drop point, DIN ISO 2176, IP 396	>= 250 °C
Four-ball tester, welding load, DIN 51350 pt. 04	approx. 3 000 N
Speed factor (n x dm)	approx. 300 000 mm/min
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	24 months

Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

Klüber Lubrication München SE & Co. KG / Geisenhausenerstraße 7 / 81379 München / Germany / phone +49 89 7876-0 / fax +49 89 7876-333.

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München SE & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München SE & Co. KG and if source is indicated and voucher copy is forwarded.