Technical Data Sheet

SAR Lubricants

Last Updated: 14.11.2006 Product Code: GR 0578

LITHIUM EP3 is a premium quality multi-purpose grease for use in all anti-friction and plain bearings subjected to high shock load and vibration conditions. Used extensively for applications throughout industry and the automotive sector.

APPLICATION

Lithium EP3 can be applied manually, or by using a standard grease gun (400 gms cartridges available), or via a central lubricating system capable of pumping an NLGI No.3 grease. As with all greases used for the first time, check compatibility with the grease applied previously and if necessary purge bearings prior to application. Likewise, as a general rule, take care not to over-lubricate and apply the quantity of grease recommended by the bearing manufacturer.

BENEFITS

- Excellent extreme pressure and anti-wear performance
- High degree of corrosion protection
- Multi-purpose grease particularly suitable for heavy duty applications

TYPICAL PROPERTIES

Appearance:	Smooth Grease	Copper Corrosion (IP 112)	Pass
Colour:	Dark Brown	Resistance To Corrosion Emcor (IP 220):	0:0
NLGI Classification:	3	Water Washout (ASTM D1264) @ 39°C %	: 3
Thickener:	Lithium Soap	Four Ball Weld Load (IP 239) kgs:	315
Base Oil:	Solvent Refined	Timken OK Load (IP 326) lbs:	50
	Mineral Oil	Oxidation Stability @ 100°C (IP142)	
Base Oil Viscosity @ 40°C (IP71) cSt:	180	Pressure Drop After 100 hrs psi:	4
Worked Penetration (IP50):	220 to 250	400 hrs psi:	14
Dropping Point (IP132) ^o C:	185 min.	Operating Temperature Range:	-20°C to +140°C
Oil Separation (IP121) %:	3 max.		

HEALTH AND SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.

SAFI LUBPHCANTS resource & PADCHUFFE & CONS LTD; Gill Bridge Oil Works, Lowlands Road, MIRFIELD, West Yorkshire, WF14 8LU Tel: +44 (0)1924 494371 Fax: +44 (0)1924 498940 Email: enquiries@sarlubricants.co.uk Registered In England: 05866783 VAT Registration No: 889171963

