


Shell Alvania Greases EP



General purpose extreme-pressure industrial grease

THICKENER	NLGI	TEMP RANGE	BASE OIL VISCOSITY	EP	WATER RESISTANCE
LITHIUM	000,00,0, 1,2	-20°C to +110°C	40°C 220 cSt	✓	☆☆

Shell Alvania Greases EP offer the excellent performance expected of the world's leading brand of grease.

They are premier quality, multipurpose, extreme-pressure industrial greases based on a blend of high viscosity index mineral oils and a lithium hydroxystreate soap thickener and contain lead free extreme-pressure and other proven additives.

Shell Alvania Greases EP are designed for the grease lubrication of rolling element and plain bearings such as those found in the steel, paper, mining, quarrying and construction industries.

Applications

Shell Alvania Greases EP R 0 & R 00 are specifically designed for:

- Steel mill lubrication where a softer grease is necessary for specialized dispensing systems.
- Heavy duty plain and rolling element bearings operating under severe conditions including shock loading in wet environments
- Gearbox applications where semi-fluid greases are required

Performance Features

- **Outstanding load carrying capacity**
Shell Alvania Greases EP contain special extreme-pressure additives which enable them to withstand heavy and shock loads without failure of the lubricant film.
- **Superior mechanical stability**
Compared to 'leaded' Alvania, the resistance to extended mechanical working is significantly improved. This is particularly important in vibrating environments where poor mechanical stability can lead to grease softening with subsequent loss of lubrication performance and leakage.
- **Excellent resistance to water wash-out**
Shell Alvania Greases EP have been formulated to offer much improved levels of resistance to water wash-out compared to the old leaded product.

- **Oxidation stability**

Specially selected base oil components have excellent oxidation resistance. Their consistency will not alter in storage and they withstand high operating temperatures without hardening or forming bearing deposits.

- **Excellent corrosion protection**

Shell Alvania Greases EP have a strong affinity with metal and have the ability to protect bearing surfaces against corrosion, even when the grease is contaminated with water.

Performance Specifications

Meet the British Timken specification for Steel Mill applications

Re-greasing Intervals

For bearings operating near their maximum recommended temperatures, re-greasing intervals should be reviewed

Health & Safety

Shell Alvania Greases EP are unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

For further guidance on Product Health & Safety refer to the appropriate Shell Product Safety Data Sheet.

Typical Physical Characteristics

Shell Alvania Grease EP	R000	R00	R0	1	2
NLGI Consistency	000	00	0	1	2
Soap Type	Lithium	Lithium	Lithium	Lithium	Lithium
Base Oil	Mineral	Mineral	Mineral	Mineral	Mineral
Kinematic Viscosity @ 40°C cSt	220	220	220	220	220
Dropping Point °C	166	168	173	180	184
Cone Penetration non-Worked Worked	446 450	413 415	358 360	320 322	282 284

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.