

Optigear Synthetic RO 220

High performance gear oil

Description

Castrol Optigear™ Synthetic RO 220 high-performance synthetic oil, developed especially for gears used in rail traffic and mechanical engineering applications (such as in Robots). The properties of Optigear Synthetic RO mean it is especially suited for hot climates.

Optigear Synthetic RO is formulated with Castrol's Microflux Trans (MFT) Plastic Deformation (PD) additive. MFT PD helps improve performance when operating temperature and loads reach a certain level of activation energy, by enabling the micro-smoothing of surface roughness without increasing wear. The smoothed surface delivers optimum wear protection and an extremely low coefficient of friction, especially in applications which experience extreme pressure, shock loads, vibrations or low speeds. MFT PD helps to protect against scuffing and shock loading, while maintaining a high load carrying capacity, and can help prevent the progression of micro-pitting in pre-damaged gears.

Application

Optigear Synthetic RO 220 can be used for all types of spur gear teeth, also under difficult load conditions. Bevel gear units, including those with a large offset (hypoid) and heavy alternating loads.

All types of roller bearings, with heavy loads and low and high temperatures. Can be used in a very broad range of temperatures, especially in hot climates.

Dip lubrication at high numbers of revolutions, as well as injection and oil mist lubrication.

Filtering (mechanical) does not result in any additive loss.

Not for synchronised gears or limited slip differentials due to low friction coefficients.

Advantages

- High pressure absorption and excellent wear protection¹
- Safe bearing lubrication in high- and low-temperature ranges
- High seizure load-bearing capacity¹
- Above-average application times – even under difficult conditions¹
- Reduction of friction coefficient and operating temperature¹
- Good corrosion protection¹
- Long service life for gears¹
- Exceeds requirements regarding wear protection in line with DIN 51517, part 3

¹When compared to conventional gear oils.

Typical Characteristics

Name	Method	Units	R0 220
Appearance	Visual	-	Blue green fluid
Density @ 15°C / 59°F	ISO 12185 / ASTM D4052	kg/m ³	875
Kinematic Viscosity @ 40°C / 104°F	ISO 3104 / ASTM D445	mm ² /s	220
Kinematic Viscosity @ 100°C / 212°F	ISO 3104 / ASTM D445	mm ² /s	23.8
Viscosity Index	ISO 2909 / ASTM D2270	-	134
Pour Point	ISO 3016 / ASTM D97	°C/°F	-45 / -49
Rust test - distilled water (24 hrs)	ISO 7120 / ASTM D665A	Rating	Pass
Copper corrosion (24 hrs@100°C/212°F)	ISO 2160 / ASTM D130	Rating	Pass
Flash Point - open cup method	ISO 2592 / ASTM D92	°C/°F	240 / 464
Water Separation @ 82°C / 180°F (40/37/3)	ISO 6614 / ASTM D1401	minutes	<30
Foam Sequence II - tendency / stability	ISO 6247 / ASTM D892	ml / ml	50 / 0
FZG Gear Scuffing test - A/8.3/90	ISO 14635-1	Failure Load Stage	>14
FZG Gear Scuffing test - A/16.6/90	ISO 14635-1	Failure Load Stage	>12
FZG Sprungtest (Jump test) - S-A10/16.6R/90	ASTM L42	Failure Load Stage	>9 (GL5 Pass)
SRV Friction and Wear test- Coefficient of friction	ASTM D6425 / DIN 51834	-	0.09

Subject to usual manufacturing tolerances.

Optigear Synthetic RO 220

30 Sep 2020

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre, Whitchurch Hill, Pangbourne, Reading, RG8 7QR, United Kingdom

<http://msdspds.castrol.com>