

PRODUCT INFORMATION



VALVOLINE™ 5TH WHEEL GREASE

Valvoline 5th Wheel Grease is designed specifically for fifth wheel top plate applications where stay in place performance is critical under all weather and application conditions. In this application, it is common for the fifth wheels to experience extreme fretting wear.

To minimize wear and increase longevity of the fifth wheel, Valvoline's formulation is built with maximum stay-in-place performance and designed to carry heavy loads during the harshest conditions. In addition, this grease contains 10% lubricating solids including moly and graphite.

Typical Properties	ASTM Method	5 th Wheel Grease
Grade	NLGI	2
Type		Lithium
Color	Visual	Black/Tacky
4-ball weld load, kg	D2596	500
Water Spray Off (% wt.)	D4049	<10%
Worked Penetration, 60 strokes	D217	265-295
Mobility @ 60F (15.6 C) g/min	US Steel	100
Rust Prevention	D1743	Pass
Lubricating Solids		10%
Base Fluid Viscosity cSt @ 40 C	D445	320

Part Numbers:	NLGI #2
120 Lb. Keg (L)	880405
35 Lb. Plastic Pail	880406

Refer to Valvoline's Safety Data Sheet for health and safety information.

This information only applies to products manufactured in the following location(s): USA, Canada.

Effective Date:
8/12/21

Author:
JB