

PRODUCT INFORMATION



VALVOLINE™ CRIMSON™ GREASE

Valvoline Crimson Grease is a preference among users with multiple grease applications, operating at moderate load carrying capacities, pressure, and temperature ranges. It is formulated with tackiness to heighten its ability to adhere to metal surfaces, and mobility for ease of pumping. This grease is fortified with an additive package that provides anti-wear protection, EP, rust and oxidation inhibition and copper corrosion resistance. Applications include: Trucking, Industrial, Agriculture and Automotive.

Valvoline Crimson Grease meets the requirements of the **NLGI LB** specification.

Typical Properties:	ASTM Method	NLGI LB
Thickener		Lithium
Color	Visual	Red
KV@40 (cSt)	D445	ISO 220
Density		7.46 lb/gal
Operating Temp Range, °F		25-250
Timken, lbs.	D2509	45
4-ball wear, scar diameter, mm	D2266	<0.6 max
4-Ball EP Load Wear Index @ XX kg	D2596	250
Load Wear Index	D2596	45
Rust Prevention	D1743	Pass
Dropping point, °F	D2265	380
Mobility @ 60°F	US Steel	350 min

Part Numbers:	NLGI LB
Bulk	VV70118
400 Lb. Drum	VV70119
120 Lb. Keg (L)	VV70120
35 Lb. Plastic Pail	VV70122
50/14 Oz. Carton	VV70124

Refer to Valvoline's Safety Data Sheet for health and safety information.

This information only applies to products manufactured in the following location(s): USA, Canada.

Effective Date:
9/10/21

Author:
JB