

PRODUCT INFORMATION



VALVOLINE™ FULL SYNTHETIC MOLY-FORTIFIED GREASE

Valvoline Full Synthetic Moly-Fortified Grease is an excellent heavy-duty and multi-purpose automotive and industrial extreme pressure grease. It consists of a lithium complex thickener in synthetic base oil and is fortified with molybdenum disulfide and other quality additives. It provides protection from high loads and may be used over a wide temperature range.

Valvoline Full Synthetic Moly-Fortified Grease is recommended for use in disc brake wheel bearings, all-purpose chassis lubrication, suspension systems, universal joints, steering linkage, and constant velocity joint applications.

Recommended Applications:

NLGI 2
NLGI GC/LB, MACK GC-G

Typical Properties	NLGI #2
NLGI Grade	2
Soap Base	Lithium Complex
Texture	Smooth
Color	Gray
ASTM Worked Penetration @ 77° F	275
ASTM Dropping Pt. °F, min	500
Rust Test (D 1743)	Pass
Timken OK Load, lbs	60
Weld Pt., kg	315
KV100, cSt	12.0
Pour Point °C	-20

Part Numbers	NLGI #2
50/14 Oz. Carton	VV985

This information only applies to products manufactured in the following location(s): USA, Canada.

Effective Date:
8/18/2021

Author:
JB