

# PRODUCT INFORMATION



## VALVOLINE™ MULTI-VEHICLE MOLY-FORTIFIED GREASE

Valvoline Multi-Vehicle Moly-Fortified Grease is a superior general purpose NLGI #2 grade lithium complex grease with molybdenum disulfide. It is designed to provide excellent extreme pressure and anti-wear protection for wheel bearings, chassis, suspension systems, steering linkage, and universal joints.

Valvoline Multi-Vehicle Moly-Fortified Grease meets Ford specification M1C75B, MACK MG-C Longlife, and NLGI LB quality requirements.

### Recommended Applications:

Ford M1C75B
MACK MG-G Longlife
NLGI GC-LB

Typical Properties	NLGI #2
NLGI Grade	2
Soap Base	Lithium Complex
Texture	Smooth
Color	Gray
ASTM Worked Penetration @ 77° F	283
ASTM Dropping Pt. °F, min	500
Rust Test (D 1743)	Pass
Timken OK Load, lbs	50
KV40, cSt	120.0
KV100, cSt	16.0
Pour Point °C	-15

Part Numbers	NLGI #2
120 Lb. Keg (L)	VV629
35 Lb. Plastic Pail	VV630
50/14 Oz. Carton	VV633

This information only applies to products manufactured in the following location(s): USA, Canada.

Effective Date:  
6/30/2021

Author:  
JB