

# PRODUCT INFORMATION



## VALVOLINE™ HEAVY DUTY PUMP GREASE

**Valvoline Heavy Duty Pump Grease** is an aluminum complex thickened lubricating grease formulated with high quality base oils and a balanced blend of performance-enhancing additives. **HD Pump Grease** withstands high heat and maintains mechanical stability when subjected to frequent temperature changes. It is fortified with extreme pressure and anti-wear additives to provide superior protection under heavy loads.

**Valvoline Heavy Duty Pump Grease** contains corrosion inhibitors to provide optimal protection of equipment from rust and deterioration, even in the presence of salt and brine. The use of oxidation inhibitors allows for longer service life and delivers consistent performance throughout the useful life of the product. **HD Pump Grease** is also exhibits high mobility making it ideal for use in centralized automatic lubrication systems.

Typical Properties:	ASTM Method	NLGI #00	NLGI #000
Thickener		Aluminum Complex	Aluminum Complex
Color	Visual	Red	Red
KV40 (cSt)	D445	238	220
Density, lbs/gal		7.5	7.77
Operating Temp Range, °F		20-200	20-200
Timken, lbs.	D2509	30	30
4-ball wear, scar diameter, mm	D2266	0.50	0.54
4-Ball EP Weld Load @ XX kg	D2596	315	315
Load Wear Index	D2596	44	----
Rust Prevention	D5969	Pass	Pass
Dropping point, °F	D2265	350	>350
Mobility @ 60°F, g/min	US Steel	545	5710

Part Numbers:	#00	#000
Tote	886058	859769
400 Lb. Drum	----	869998
120 Lb. Keg (L)	----	870024
35 Lb. Plastic Pail	----	869999

Refer to Valvoline's Safety Data Sheet for health and safety information.

This information only applies to products manufactured in the following location(s): USA, Canada.

Effective Date:  
9/21/21

Author:  
KD