



# Shell Alvania Grease 1029

## DESIGNED TO MEET CHALLENGES

### Specifications, Approvals & Recommendations

- AUMA

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

### Typical Physical Characteristics

Properties	Method	Shell Alvania Grease 1029
NLGI Class		00/000
Colour		Red
Thickener system		LiCa
Kinematic Viscosity @40°C mm <sup>2</sup> /s	ASTM D445	40

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

### Health, Safety & Environment

- Health and Safety

Shell Alvania 1029 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.shell.com/>

- Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

### Additional Information

- Operating Temperature Range

Shell Alvania 1029 operation temperature is from -40°C up to 80°C.

- Advice

Advice on applications not covered here may be obtained from your Shell representative.