

# ECO TRUCK CD 50



**BEHTAM**  
RAVANKAR

## Data sheet

Monograde Oil For Diesel Engines

### APPLICATIONS

#### Uses

- All Diesel turbocharged or normally aspirated engines.

### PERFORMANCES

#### Specifications

- API CD

### CUSTOMER BENEFITS

#### Technical

- Monograde
- High viscosity index
- High detergent level
- High dispersancy level
- Good anti-wear, anti-corrosion properties
- Good anti-rust, anti-oxidant, anti-foaming properties.

### CHARACTERISTICS

ECO TRUCK CD 50	Method	Units	SAE Grade 50
Volumetric mass at 15°C	ASTM D1298	kg/m <sup>3</sup>	900
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	235
Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	19.25
Viscosity Index	ASTM D2270	-	90
Pour Point	ASTM D97	°C	-15
Flash Point	ASTM D92	°C	250

The typical characteristics mentioned represent mean values.

**BEHTAM CO.**  
ECO TRUCK CD 50

[www.btoil.co](http://www.btoil.co)

1/1

### ECO TRUCK CD 50

This lubricant, when used according to our recommendations and for the purpose for which is intended, presents no particular hazards. A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.