

ECO TRUCK CF-4 40



Mineral lubricant suitable for diesel engines.

SPECIFICATIONS

Meets the requirements of

API CF-4

APPLICATIONS

BEHTAM ECO TRUCK CF 40 is a mineral lubricant recommended for old diesel engines of transport, public works materials, agricultural vehicles...

It is also suitable for stationary engines.

BEHTAM ECO TRUCK CF 40 is suitable for all diesel engines when an SAE 40 grade lubricant is recommended.

PERFORMANCES AND CUSTOMER BENEFITS

BEHTAM ECO TRUCK CF 40 exhibits good resistance to oxidation, preventing the formation of deposits and varnishes.

Detergent, dispersant and anti-wear properties keep the **engine clean** and enable effective control of soot, sludge and piston deposits.













PHYSICAL AND CHEMICAL CHARACTERISTICS*

| BEHTAM ECO TRUCK CF 40 | | Method | Value |
|------------------------------|-------------------|------------|-------|
| Density at 15°C | kg/m ³ | ASTM D4052 | 890 |
| Kinematic Viscosity at 40°C | mm²/s | ASTM D445 | 165 |
| Kinematic Viscosity at 100°C | mm²/s | ASTM D445 | 15.5 |
| Viscosity Index | - | ASTM D2270 | 95 |
| Flash point | °C | ASTM D92 | >250 |
| Pour point | °C | ASTM D97 | -24 |
| T.B.N | mgKOH/g | ASTM D2896 | 11.5 |
| Sulphated Ash | % m/m | ASTM D874 | 1.52 |

^{*} The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

RECOMMENDATIONS

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements.

The product should not be stored at a temperature above 60 °C. Exposure to strong sunlight, extreme cold or high temperature variations must be avoided.

All packages should be protected from bad weather conditions. The drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.

HEALTH, SAFETY AND ENVIRONMENT

Based on available information, this product does not cause adverse health effects when used in the intended application and the recommendations provided in the Safety Data Sheet (MSDS) are followed.

This product should not be used for applications other than those for which it is intended.

If disposing of used product, take care to protect the environment and comply with local regulations.









