



ECO TRUCK CH-4 15W40



Mineral lubricant for **diesel** engines, suitable for **on-road** applications.

SPECIFICATIONS

Meets the requirements of

ACEA E7

API CH-4/SJ

- ✓ Cummins CES 20071/72/76
- ✓ Mack EOM Plus
- ✓ MAN M 3275
- ✓ MB-Approval 228.3
- ✓ Renault Trucks RD/RD-2
- ✓ Volvo VDS-2
- ✓ MTU 2.0

APPLICATIONS

BEHTAM ECO TRUCK CH-4 15W40 is a **mineral** lubricant used in **diesel on-road** applications (trucks, buses...).

BEHTAM ECO TRUCK CH-4 15W40 is particularly adapted to **Euro 3** and previous engine generations, such as **Renault Trucks** and **Mercedes-Benz** vehicles.

PERFORMANCES AND CUSTOMER BENEFITS

Detergent, antioxidant and anti-corrosion additives help to reach **standard oil drain intervals** defined by the manufacturer.

Detergent, dispersant and anti-wear properties keep the **engine clean** and enable efficient control of soot, sludge and piston deposits.

PHYSICAL AND CHEMICAL CHARACTERISTICS*

BEHTAM ECO TRUCK CH-4 15W40

		Method	Value
Density at 15°C	kg/m ³	ASTM D4052	885
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	111.0
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	14.4
Viscosity Index	-	ASTM D2270	132
Flash point	°C	ASTM D92	230
Pour point	°C	ASTM D97	-30
T.B.N	mgKOH/g	ASTM D2896	10
Sulphated Ash	% m/m	ASTM D874	1.45

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

RECOMMENDATIONS

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements.

The product should not be stored at a temperature above 60 °C. Exposure to strong sunlight, extreme cold or high temperature variations must be avoided.

All packages should be protected from bad weather conditions. The drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.

HEALTH, SAFETY AND ENVIRONMENT

Based on available information, this product does not cause adverse health effects when used in the intended application and the recommendations provided in the Safety Data Sheet (MSDS) are followed.

This product should not be used for applications other than those for which it is intended.

If disposing of used product, take care to protect the environment and comply with local regulations.