



ECO TRUCK CI-4 15W40



Mineral lubricant suitable for on-road diesel engines.

SPECIFICATIONS

Meets the requirements of:

ACEA E7

API CI-4/SL

- | | |
|---------------------------|----------------------|
| ✓ Cummins CES 20076/77/78 | ✓ Caterpillar ECF-1a |
| ✓ Kamaz | ✓ DAF |
| ✓ Mack EO-M PLUS | ✓ IVECO |
| ✓ MAN M 3275 | ✓ Scania |
| ✓ MB-Approval 228.3 | |
| ✓ Renault Trucks RLD-2 | |
| ✓ Volvo VDS-3 | |
| ✓ MTU 2.0 | |

APPLICATIONS

BEHTAM ECO TRUCK CI-4 15W40 is a mineral lubricant used in on-road diesel technology.

It is recommended to Euro 3, and previous engines of most European and American manufacturers.

BEHTAM ECO TRUCK CI-4 15W40 enables coverage some fleet of mixed brands (American and European manufacturers) with a minimal number of products.

PERFORMANCES AND CUSTOMER BENEFITS

BEHTAM ECO TRUCK CI-4 15W40 contains excellent viscosity stability in service, guaranteeing effective engine lubrication in severe conditions.

Outstanding detergent, dispersant and anti-wear properties keep the engine clean and enable efficient control of soot, sludge and piston deposits.

Piston cleanliness performance affords effective protection against cylinder liner polishing.

PHYSICAL AND CHEMICAL CHARACTERISTICS*

| BEHTAM ECO TRUCK CI-4 15W40 | | Method | Value |
|------------------------------------|--------------------|---------------|--------------|
| Density at 15°C | kg/m ³ | ASTM D4052 | 888 |
| Kinematic Viscosity at 40°C | mm ² /s | ASTM D445 | 110.1 |
| Kinematic Viscosity at 100°C | mm ² /s | ASTM D445 | 14.4 |
| Viscosity Index | - | ASTM D2270 | 136 |
| Flash point | °C | ASTM D92 | 230 |
| Pour point | °C | ASTM D97 | -30 |
| T.B.N | mgKOH/g | ASTM D2896 | 11 |
| Sulphated Ash | % m/m | ASTM D874 | 1.45 |

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

RECOMMENDATIONS

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements.

The product should not be stored at a temperature above 60°C. Exposure to strong sunlight, extreme cold or high temperature variations must be avoided.

All packages should be protected from bad weather conditions. The drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.

HEALTH, SAFETY AND ENVIRONMENT

Based on available information, this product does not cause adverse health effects when used in the intended application and the recommendations provided in the Safety Data Sheet (MSDS) are followed.

This product should not be used for applications other than those for which it is intended.

If disposing of used product, take care to protect the environment and comply with local regulations.