

SARGREASE CBS 2 is a superior quality, calcium sulphonate complex grease designed to provide exceptional load carrying capability and provide extended lubrication intervals in a wide range of applications.

APPLICATION

Specially developed for the lubrication of all types of plain and anti-friction bearings as well as sliding surfaces which require enhanced levels of water resistance and corrosion protection.

Can be applied by hand, by using a standard grease gun or via a central lubricating system compatible with an NLGI 2 grease.

Please check compatibility before application and use in accordance with equipment manufacturers recommendations.

BENEFITS

- Extends re-lubrication intervals to ensure maximum economy in use and reduced grease consumption
- Highly water resistant formulation offers excellent corrosion protection even when operating in wet conditions or open to the elements
- Excellent EP and anti-wear performance for all types of plain/anti-friction bearings and sliding surfaces

TYPICAL PROPERTIES

Appearance:	Smooth, beige grease
Thickener:	Calcium Sulphonate Complex
NLGI Classification:	No.2
Base Oil Viscosity@40°C (IP71):	220 cSt
Water Washout (IP215, ASTM D1264):	<1%
Dropping Point (ASTM D1264):	>280°C
Operating temperature range:	-30°C to +150°C, occasional peak to 220°C

HEALTH AND SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.