

Last Updated: 31.03.2017
Product Code: GR0906/3KG

WHITE BRAKE GREASE is a premium quality, water-resistant, NLGI 2 grease designed for use where exceptional corrosion protection and performance is required.

APPLICATION

Designed primarily to protect and lubricate brake backing plates and piston housings. Its exceptional properties make it also ideal for marine and industrial applications where high levels of lubricating performance and corrosion protection are specified to combat wet or humid environments. Special additive technology provides additional protection and lubrication where excessive levels of water are prevalent, such as in water pumping equipment. It is also suitable for marine use as Stern Tube grease, and is compatible for use with both plain and anti-friction bearings. Please check compatibility before application and use in accordance with equipment manufacturers recommendations.

BENEFITS

- Exceptionally high level of water resistance
- Excellent corrosion protection even in the most humid of environments
- Good sealing properties

PERFORMANCE PROFILE

ISO 6743-9: L-XBCHA2
DIN 51502: KF2G-20

TYPICAL PROPERTIES

Appearance:	Off-white smooth grease	Operating temperature range:	-20°C to + 110°C
NLGI classification:	2	Water washout (ASTM D1264)	
Base Oil:	Highly refined mineral oil	- @38°C:	2%
Thickener:	Calcium 12 hydroxy stearate	- @79°C:	5%
Zinc oxide content:	5%	Dropping point (IP132):	+ 140°C min

HEALTH AND SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.